

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: DELGLAZE

Product code: C3-1114

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Delvemade Ltd
Bankfield Mills
Bankfield Street
Stoneclough, Radcliffe
Manchester
M26 1AS
United Kingdom

Tel: +44 (0) 1204 868 604

Fax: +44 (0) 1204 862 332

Email: tom.armitt@delvemade.com

1.4. Emergency telephone number

Emergency tel: +44 (0) 1204 573 736

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 3: H226; Aquatic Chronic 3: H412; -: EUH208

Most important adverse effects: Contains 3-isocyanatomethyl-3,5,5-trimethylcyclohexylisocyanate, tinuvin 1130, tinuvin 292, hardener hy 1120. May produce an allergic reaction. Flammable liquid and vapour. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: EUH208: Contains 3-isocyanatomethyl-3,5,5-trimethylcyclohexylisocyanate, tinuvin 1130, tinuvin 292, hardener hy 1120. May produce an allergic reaction.
H226: Flammable liquid and vapour.
H412: Harmful to aquatic life with long lasting effects.

Signal words: Warning

Hazard pictograms: GHS02: Flame



[cont...]



Delvemade Limited

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240: container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting/.. equipment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P370+378: In case of fire: Use to extinguish.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

2-METHOXY-1-METHYLETHYL ACETATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
203-603-9	108-65-6	Substance with a Community workplace exposure limit.	Flam. Liq. 3: H226	10-30%

2,6-DIMETHYLHEPTAN-4-ONE

203-620-1	108-83-8	-	Flam. Liq. 3: H226; STOT SE 3: H335	10-30%
-----------	----------	---	-------------------------------------	--------

XYLENE

215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	1-10%
-----------	-----------	---	---	-------

TINUVIN 1130

-	-	-	-	<1%
---	---	---	---	-----

TINUVIN 292

-	-	-	-	<1%
---	---	---	---	-----

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLISOCYANATE

223-861-6	4098-71-9	-	Acute Tox. 3: H331; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317; Aquatic Chronic 2: H411	<1%
-----------	-----------	---	--	-----

HARDENER HY 1120

247-094-1	25550-51-0	-	-	<1%
-----------	------------	---	---	-----

Section 4: First aid measures

[cont...]



Delvemade Limited

Bankfield Mills, Stoneclough, Radcliffe, Manchester M26 1AS Tel +44(0)1204 868604 Fax +44(0)1204 862332
www.delvemade.co.uk Email contact@delvemade.com Delvemade is an independent subsidiary of Itac Limited www.itacadhesives.co.uk

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Notify the police and fire brigade immediately. Eliminate all sources of ignition. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

[cont...]



6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage**7.1. Precautions for safe handling**

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection**8.1. Control parameters**

Hazardous ingredients:

2-METHOXY-1-METHYLETHYL ACETATE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	274 mg/m ³	822 mg/m ³	-	-

2,6-DIMETHYLHEPTAN-4-ONE

UK	148 mg/m ³	-	-	-
----	-----------------------	---	---	---

XYLENE

UK	100PPM	150PPM	-	-
----	--------	--------	---	---

TINUVIN 1130

UK	1MG/M	-	-	-
----	-------	---	---	---

TINUVIN 292

UK	1 mg/M ³	-	-	-
----	---------------------	---	---	---

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLISOCYANATE

UK	0.02 mg/m ³	0.07 mg/m ³	-	-
----	------------------------	------------------------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

[cont...]



Cutting Edge Technology

Delvemade Limited

Bankfield Mills, Stoneclough, Radcliffe, Manchester M26 1AS Tel +44(0)1204 868604 Fax +44(0)1204 862332
www.delvemade.co.uk Email contact@delvemade.com Delvemade is an independent subsidiary of Itac Limited www.itacadhesives.co.uk

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Blue

Odour: Nauseating

Evaporation rate: Slow

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: Non-viscous

Kinematic viscosity: 5000CPS

Viscosity test method: Kinematic viscosity in 10⁻⁶ m²/s at 40°C (ISO 3104/3105)

Flash point°C: 54

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

[cont...]



10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information**11.1. Information on toxicological effects****Hazardous ingredients:****2-METHOXY-1-METHYLETHYL ACETATE**

IPR	MUS	LD50	750	mg/kg
ORL	RAT	LD50	8532	mg/kg

2,6-DIMETHYLHEPTAN-4-ONE

ORL	MUS	LD50	1416	mg/kg
ORL	RAT	LD50	5750	mg/kg

XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

TINUVIN 1130

ORL	RAT	LD50	>2000	mg/kg
-----	-----	------	-------	-------

TINUVIN 292

ORL	RAT	LD50	>2000	mg/kg
-----	-----	------	-------	-------

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLISOCYANATE

ORL	MUS	LDLO	2500	µl/kg
ORL	RAT	LD50	4825	mg/kg
SKN	RAT	LDLO	1	ml/kg

HARDENER HY 1120

ORL	RAT	LD50	>5000	mg/kg
-----	-----	------	-------	-------

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

[cont...]



Cutting Edge Technology

Delvemade Limited

Bankfield Mills, Stoneclough, Radcliffe, Manchester M26 1AS Tel +44(0)1204 868604 Fax +44(0)1204 862332
www.delvemade.co.uk Email contact@delvemade.com Delvemade is an independent subsidiary of Itac Limited www.itacadhesives.co.uk

Section 12: Ecological information**12.1. Toxicity**

Hazardous ingredients:

TINUVIN 1130

MAGNA	48H EC50	3.80	mg/l
BLUEGILLS	96H LC50	2.80	mg/l

TINUVIN 292

BLUEGILLS	96H LC50	0.97	mg/l
RAINBOW TROUT	96H LC50	7.90	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations**13.1. Waste treatment methods**

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information**14.1. UN number**

UN number: UN1866

14.2. UN proper shipping name

Shipping name: RESIN SOLUTION

[cont...]



Cutting Edge Technology

Delvemade Limited

Bankfield Mills, Stoneclough, Radcliffe, Manchester M26 1AS Tel +44(0)1204 868604 Fax +44(0)1204 862332
www.delvemade.co.uk Email contact@delvemade.com Delvemade is an independent subsidiary of Itac Limited www.itacadhesives.co.uk

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 2

Section 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment**Section 16: Other information****Other information**

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.

H226: Flammable liquid and vapour.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

[final page]

