

SAFETY DATA SHEET

SEAMSIL - TOP COAT. (VARIOUS COLOURS).

Page: 1

Compilation date: 20/05/2014

Revision date: 29/03/2016

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: SEAMSIL - TOP COAT. (VARIOUS COLOURS).

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Delvemade Ltd
Bankfield Mills
Bankfield Street
Stoneclough, Radcliffe
Manchester
M26 1AS
United Kingdom

Tel: +44 (0) 1204 868 604

Fax: +44 (0) 1204 862 332

Email: tom.armitt@delvemade.com

1.4. Emergency telephone number

Emergency tel: +44 (0) 1204 573 736

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 2: H411; Flam. Liq. 2: H225; Skin Irrit. 2: H315

Most important adverse effects: Highly flammable liquid and vapour. Causes skin irritation. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H225: Highly flammable liquid and vapour.
H315: Causes skin irritation.
H411: Toxic to aquatic life with long lasting effects.

Signal words: Danger

Hazard pictograms: GHS02: Flame
GHS07: Exclamation mark
GHS09: Environmental



[cont...]



Cutting Edge Technology

Delvemade Limited

Bankfield Mills, Stoneclough, Radcliffe, Manchester M26 1AS Tel +44(0)1204 868604 Fax +44(0)1204 862332
www.delvemade.co.uk Email delvemade@itac.uk.com Delvemade is an independent subsidiary of Itac Limited www.itacadhesives.co.uk

SAFETY DATA SHEET

SEAMSIL - TOP COAT. (VARIOUS COLOURS).

Page: 2

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241: Use explosion-proof electrical/ventilating/lighting/.. equipment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P302+352: IF ON SKIN: Wash with plenty of water/..
P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P321: Specific treatment (see instructions on this label).

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

CYCLOHEXANE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
203-806-2	110-82-7	-	Flam. Liq. 2: H225; Asp. Tox. 1: H304; Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 1: H410; Aquatic Acute 1: H400	10-30%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.
Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.
Ingestion: Wash out mouth with water. Consult a doctor.
Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.
Eye contact: There may be irritation and redness. The eyes may water profusely.
Ingestion: There may be soreness and redness of the mouth and throat.
Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

[cont...]



Cutting Edge Technology

Delvemaded Limited

Bankfield Mills, Stoneclough, Radcliffe, Manchester M26 1AS Tel +44(0)1204 868604 Fax +44(0)1204 862332
www.delvemaded.co.uk Email delvemaded@itac.uk.com Delvemaded is an independent subsidiary of Itac Limited www.itacadhesives.co.uk

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

[cont...]



8.1. Control parameters**Hazardous ingredients:****CYCLOHEXANE****Workplace exposure limits:****Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	350 mg/m ³	1050 mg/m ³	-	-

DNEL/PNEC Values**DNEL / PNEC** No data available.**8.2. Exposure controls****Engineering measures:** Ensure there is sufficient ventilation of the area.**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.**Hand protection:** Protective gloves.**Eye protection:** Safety glasses. Ensure eye bath is to hand.**Skin protection:** Protective clothing.**Section 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties****State:** Liquid**Odour:** Perceptible odour**Evaporation rate:** Moderate**Solubility in water:** Insoluble**Also soluble in:** Most organic solvents.**Viscosity:** Viscous**Kinematic viscosity:** PAINT LIKE**Viscosity test method:** Kinematic viscosity in 10⁻⁶ m²/s at 40°C (ISO 3104/3105)**Boiling point/range°C:** >35**Flash point°C:** <23**Relative density:** 1.21**9.2. Other information****Other information:** No data available.**Section 10: Stability and reactivity****10.1. Reactivity****Reactivity:** Stable under recommended transport or storage conditions.**10.2. Chemical stability****Chemical stability:** Stable under normal conditions.

[cont...]



Cutting Edge Technology

Delvemade LimitedBankfield Mills, Stoneclough, Radcliffe, Manchester M26 1AS Tel +44(0)1204 868604 Fax +44(0)1204 862332
www.delvemade.co.uk Email delvemade@itac.uk.com Delvemade is an independent subsidiary of Itac Limited www.itacadhesives.co.uk

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information**11.1. Information on toxicological effects**

Hazardous ingredients:

CYCLOHEXANE

ORL	MUS	LD50	813	mg/kg
ORL	RAT	LD50	12705	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information**12.1. Toxicity**

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

[cont...]



Cutting Edge Technology

Delvemad Limited

Bankfield Mills, Stoneclough, Radcliffe, Manchester M26 1AS Tel +44(0)1204 868604 Fax +44(0)1204 862332
www.delvemad.co.uk Email delvemad@itac.uk.com Delvemad is an independent subsidiary of Itac Limited www.itacadhesives.co.uk

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

[cont...]



Cutting Edge Technology

Delvemade Limited

Bankfield Mills, Stoneclough, Radcliffe, Manchester M26 1AS Tel +44(0)1204 868604 Fax +44(0)1204 862332
www.delvemade.co.uk Email delvemade@itac.uk.com Delvemade is an independent subsidiary of Itac Limited www.itacadhesives.co.uk

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H225: Highly flammable liquid and vapour.
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.
H336: May cause drowsiness or dizziness.
H410: Very toxic to aquatic life with long lasting effects.
H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

[final page]



Cutting Edge Technology

Delvemade Limited

Bankfield Mills, Stoneclough, Radcliffe, Manchester M26 1AS Tel +44(0)1204 868604 Fax +44(0)1204 862332
www.delvemade.co.uk Email delvemade@itac.uk.com Delvemade is an independent subsidiary of Itac Limited www.itacadhesives.co.uk